



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-SIL

ALUMINIZED
AMI-SIL CLOTH
STYLE #AAS3600
10/08

STYLE NO: AAS3600

NOMINAL WIDTH: 36"

NOMINAL BASE FABRIC WEIGHT: 36.0 OZ/YD2

NOMINAL FINISHED WEIGHT: 40.0 OZ/YD2

NOMINAL THICKNESS: 0.055"

METALIZED POLYESTER FILM: .001" THICK

BASE CLOTH TEMPERATURE RESISTANCE: 1800° F

METALIZED POLYESTER FILM TEMPERATURE RESISTANCE: 450° F

ADHESIVE TEMPERATURE RESISTANCE: 300° F

BASE FABRIC CONTENT: 96% SILICA (MINIMUM)

BASE FABRIC WEAVE: 12 HARNESS SATIN

COUNT: WARP: 44

FILL: 32

NOTE: WIDTH OF FINISHED FABRIC MAY BE AS MUCH AS 1-2" NARROWER THAN STATED WIDTH, DUE TO ALUMINIZATION PROCESS.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03

Date Revised: 10/08

Date Reviewed: 09/08

Revision No.: 1

DOCUMENT IS UNCONTROLLED IF PRINTED