



Auburn Manufacturing Inc.  
P.O. Box 220  
Mechanic Falls, Maine 04256  
U.S.A. 1-800-AMI-6689 • 207-345-8271  
FAX: 207-345-3380

## AMI-SIL

AMI-SIL LOW DENSITY ROPE  
STYLE #ASR-LD  
01/03

STYLE NO: ASR-LD

TEMPERATURE RESISTANCE: 1800° F

CONTENT: 96% SILICA (MINIMUM)

CONSTRUCTION: KNITTED

STYLE	DIAMETER	FT/LB	FT/CASE
ASR375LD	3/8"	69.2	1153
ASR500LD	1/2"	39.2	653
ASR625LD	5/8"	26.0	433
ASR750LD	3/4"	19.2	320
ASR875LD	7/8"	11.0	183
ASR1000LD	1"	9.3	155
ASR1250LD	1 1/4"	5.6	93
ASR1500LD	1 1/2"	3.8	63

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

NOTE: THERE MAY BE SEVERAL SPLICES PER CASE

---

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03

Date Revised:

Date Reviewed: 09/08

Revision No.: 0

DOCUMENT IS UNCONTROLLED IF PRINTED