

## AMI-SIL

AMI-SIL CLOTH  
STYLE #CAS1200  
04/07

STYLE: CAS1200

WIDTH: 36"

NOMINAL WEIGHT: 12.5 OZ/YD<sup>2</sup>

NOMINAL THICKNESS: 0.028"

TEMPERATURE RESISTANCE: 1800°F

MELTING POINT: 3000°F

CONTENT: 96% SILICA (MINIMUM)

WEAVE: PLAIN

COUNT: WARP: 19

FILL: 14



THIS PRODUCT HAS BEEN TESTED AND FM APPROVED AS A *WELDING CURTAIN* TO ANSI/FM 4950 FOR HOT WORK PROTECTION. TEST DATA AVAILABLE UPON REQUEST. REFERENCE PROJECT ID # 3015367.

SPECIAL MARKINGS: PRODUCT MARKED IN ACCORDANCE WITH FM APPROVAL STANDARD 4950 INCLUDING DESIGNATION AS A ***WELDING CURTAIN*** AND WITH USES AND LIMITATIONS INFORMATION.

NOTES: ABRASION RESISTANT COATING AVAILABLE FOR ADDED DURABILITY

ALSO AVAILABLE WITH A HIGH PERFORMANCE PRESSURE SENSITIVE ADHESIVE

ADHESIVE TEMPERATURE RESISTANCE: 300°F

ADHESIVE IS ONLY USED TO AID IN THE INSTALLATION PROCESS. AFTER THE MATERIAL IS IN PLACE IT IS USUALLY MECHANICALLY BONDED SO THAT THE ADHESIVE IS NO LONGER NECESSARY.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

---

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 04/07

Date Revised:

Date Reviewed: 09/08

Revision No.: 0

DOCUMENT IS UNCONTROLLED IF PRINTED