



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

CARBO-FLEX®

AMI-FLEX CLOTH
STYLE# FLP3001
01/2010

STYLE #: FLP3001

DESCRIPTION: 100% PREOX NONWOVEN COMBINED WITH A FABRIC WOVEN FROM YARNS WITH A PREDOMINANTLY PARA-ARAMID OUTER LAYER AND A FIBERGLASS INNER CORE.

NOMINAL WIDTH: 40" OR 60"

NOMINAL WEIGHT: 30.0 OZ/YD²

NOMINAL THICKNESS: 0.145"

TEMPERATURE RESISTANCE:	FIBERGLASS	1000°F
	ARAMID	600°F
	PREOX	500°F

NOTE: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 12/09

Date Revised: 01/27/10

Date Reviewed: 01/26/2010

Revision No.: 1

DOCUMENT IS UNCONTROLLED IF PRINTED