

AMI-GLAS

AMI-GLAS CLOTH
STYLE #GL1300
03/06

STYLE NO: GL1300 *

FABRIC FINISH: PLAIN OR 9383 (HEAT CLEANED)

NOMINAL WIDTH: 60"

NOMINAL WEIGHT: 13.0 OZ/YD²

NOMINAL THICKNESS: 0.016"

TEMPERATURE RESISTANCE: 1000° F

CONTENT: 100% FIBERGLASS YARNS

WEAVE: 4 HARNESS SATIN

COUNT: WARP: 48
FILL: 31

ALL UNCOATED FIBERGLASS YARNS MEET USCG 164.009 "TEST FOR INCOMBUSTIBILITY"

AVAILABLE WITH A HIGH PERFORMANCE PRESSURE SENSITIVE ADHESIVE

- ADHESIVE TEMPERATURE RESISTANCE: 300° F
- ADHESIVE IS ONLY USED TO AID THE INSTALLATION PROCESS, AFTER THE MATERIAL IS IN PLACE, IT IS USUALLY MECHANICALLY BONDED SO THAT THE ADHESIVE IS NO LONGER NECESSARY.

RAVEL RESISTANCE COATING AVAILABLE - SEE COATINGS SPEC SHEET FOR OPTIONS.

NOTE: COATING FINISHES DECOMPOSE AT TEMPERATURES BELOW THE BASE FABRICS TEMPERATURE RESISTANCE.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

*** COLORS ARE COVERED UNDER A DIFFERENT SPECIFICATION SHEET**

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 03/06

Date Revised:

Date Reviewed: 08/08

Revision No.:

DOCUMENT IS UNCONTROLLED IF PRINTED