

AMI-GLAS

AMI-GLAS CLOTH
STYLE #GL2401
09/08

STYLE NO: GL2401 All Colors *

FABRIC FINISH: PLAIN

NOMINAL WIDTH: 40", 60" OR 72"

NOMINAL WEIGHT: 24.0 OZ/YD²

NOMINAL THICKNESS: 0.055"

TEMPERATURE RESISTANCE: 1000° F

CONTENT: 100% FIBERGLASS YARNS

WEAVE: PLAIN

COUNT: WARP: 20
FILL: 11

NOMINAL BREAK STRENGTH: WARP: 200 PPI
FILL: 400 PPI

NFPA701/1999
MEETS THE REQUIREMENTS OF TEST METHOD 1
TEST REPORTS ON FILE



THIS PRODUCT HAS BEEN TESTED AND FM APPROVED AS A *WELDING CURTAIN* TO ANSI/FM 4950 FOR HOT WORK PROTECTION. TEST DATA AVAILABLE UPON REQUEST. REFERENCE PROJECT ID # 3020654.

SPECIAL MARKINGS: PRODUCT MARKED IN ACCORDANCE WITH FM APPROVAL STANDARD 4950 INCLUDING DESIGNATION AS A **WELDING CURTAIN** AND WITH USES AND LIMITATIONS INFORMATION.

ALL UNCOATED FIBERGLASS YARNS MEET USCG 164.009 "TEST FOR INCOMBUSTIBILITY"

AVAILABLE WITH A HIGH PERFORMANCE PRESSURE SENSITIVE ADHESIVE UP TO 60" WIDE

- ADHESIVE TEMPERATURE RESISTANCE: 300° F
- ADHESIVE IS ONLY USED TO AID THE INSTALLATION PROCESS, AFTER THE MATERIAL IS IN PLACE, IT IS USUALLY MECHANICALLY BONDED SO THAT THE ADHESIVE IS NO LONGER NECESSARY.

RAVEL RESISTANCE COATING AVAILABLE - SEE COATINGS SPEC SHEET FOR OPTIONS.

NOTE: COATING FINISHES DECOMPOSE AT TEMPERATURES BELOW THE BASE FABRICS TEMPERATURE RESISTANCE.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

* Heat Cleaned Cloth is covered under separate spec sheet

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 04/07

Date Revised: 09/08

Date Reviewed: 08/08

Revision No.: 1

DOCUMENT IS UNCONTROLLED IF PRINTED