



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-TUF

AMI-TUF CLOTH
STYLE #SGLHB2000
10/08

STYLE NO: SGLHB2000

NOMINAL WIDTH: 38"

NOMINAL FINISHED FABRIC WEIGHT: 20.0 OZ/YD² + 10%

NOMINAL FINISHED FABRIC THICKNESS: 0.025" + 10%

STANDARD COLORS: RED OR GRAY

COATING TEMPERATURE RESISTANCE: 500^o F

BASE FABRIC TEMPERATURE RESISTANCE: 1000^o F

CONTENT: 100% FIBERGLASS CLOTH WITH CURED SILICONE RUBBER ON TWO SIDES

WEAVE: HERRINGBONE

NOMINAL BREEAKING STRENGTH: WARP X FILL: 300 X 300 LBS/IN MIN AVE

NOMINAL TEAR STRENGTH: WARP X FILL: 35 X 35 LBS MIN AVE

TEST METHOD INFORMATION AVAILABLE - SEE TEST METHOD SUMMARY SHEET

SGLHB IS A FIBERGLASS BASE FABRIC WHICH HAS BEEN COATED WITH OUR SPECIALLY FORMULATED SILICONE RUBBER COMPOUND. THIS SILICONE COATING EXTENDS LIFE AND EASE OF FABRICATION WHILE PROVIDING GREATER OIL AND WATER RESISTANCE THAN UNCOATED FABRICS AS WELL AS LOW SMOKE AND FLAME RETARDANCY.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 03/07

Date Revised: 10/08

Date Reviewed: 09/08

Revision No.: 1

DOCUMENT IS UNCONTROLLED IF PRINTED