



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

VEXTRA

VEXTRA CLOTH
STYLE #SGLV3001-1
11/04

STYLE NO: SGLV3001-1

NOMINAL FABRIC WIDTH: 40" OR 60"

NOMINAL FABRIC WEIGHT: 39.0 OZ/YD²

NOMINAL FABRIC THICKNESS: 0.070"

BASE FABRIC: PLAIN WEAVE 100% FIBERGLASS CLOTH TREATED WITH VERMICULITE

COUNT: WARP: 19
FILL: 8

TEMPERATURE RESISTANCE: FABRIC IS RATED AT 500° F CONTINUOUS, REMAINS STABLE TO 1500° F WITH VERMICULITE COATING. FIBERGLASS BASE FABRIC IS RATED AT 1000° F.

FABRIC FINISH: ON ONE SIDE IS A VERMICULITE INORGANIC COATING, CHEMICALLY INERT, NONCUMBUSTIBLE, & ODORLESS. ON THE OTHER SIDE A SILICONE RUBBER COMPOUND.

NOTE: WIDTH OF FINISHED PRODUCT MAY BE NARROWER DUE TO SHRINKAGE DURING COATING.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 11/04

Date Revised:

Date Reviewed: 09/08

Revision No.: 0

DOCUMENT IS UNCONTROLLED IF PRINTED