

Auburn Manufacturing Inc. P.O. Box 220 Mechanic Falls, Maine 04256 U.S.A. 1-800-AMI-6689 • 207-345-8271

FAX: 207-345-3380

## **AMI-SIL**

AMI-SIL CLOTH STYLE# AAS1800F 04/18

STYLE #: AAS1800F NOMINAL WIDTH: 36"

NOMINAL BASE FABRIC WEIGHT: 18.0 OZ/YD<sup>2</sup> NOMINAL FINISHED WEIGHT: 22.0 OZ/YD<sup>2</sup>

NOMINAL THICKNESS: 0.035"

METALIZED POLYESTER FILM: .001" THICK

BASE CLOTH TEMPERATURE RESISTANCE: 1800°F

METALIZED POLYESTER FILM TEMPERATURE RESISTANCE: 450°F

ADHESIVE TEMPERATURE RESISTANCE: 300°F

BASE FABRIC CONTENT: 96% AMORPHOUS SILICA (MINIMUM)

BASE FABRIC WEAVE: 4 HARNESS CROW'S FOOT

COUNT: WARP: 30 FILL: 17

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY

FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO

FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

NOTE: WIDTH OF FINISHED PRODUCTS MAY BE NARROWER DUE TO THE LAMINATION PROCESS

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.