



**Made in USA of Domestic and/or Imported Materials**

**PRODUCT DATA SHEET**


AMI-SIL® – Style No: AAS2400

For additional information please contact [sales@auburnmfg.com](mailto:sales@auburnmfg.com)

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	36 in	91.4 cm
NOMINAL BASE FABRIC WEIGHT:	24.0 OZ/YD <sup>2</sup>	814 g/m <sup>2</sup>
NOMINAL FINISHED WEIGHT:	25.0 OZ/YD <sup>2</sup>	848 g/m <sup>2</sup>
NOMINAL THICKNESS:	0.040 in	1.016 mm
BASE FABRIC COUNT & WEAVE:	WARP: 30 yarns/in FILL: 22 yarns/in HERRINGBONE WEAVE	WARP: 11.8 yarns/cm FILL: 8.7 yarns/cm HERRINGBONE WEAVE
BASE CLOTH TEMPERATURE RESISTANCE:	1800° F	982° C
METALIZED POLYESTER FILM TEMPERATURE RESISTANCE:	450° F	232° C
ADHESIVE TEMPERATURE RESISTANCE:	450° F	232° C

**PRODUCT HIGHLIGHTS**

- ❖ Base Fabric Content: 96% Amorphous Silica (Minimum).
- ❖ Width of finished products may be narrower due to the lamination process. Width tolerance after lamination is 33” – 36”.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.