



**Made in USA of Domestic and/or Imported Materials**

## PRODUCT DATA SHEET

AMI-GLAS® – Style No: AMGL2025

For additional information please contact [sales@auburnmfg.com](mailto:sales@auburnmfg.com)

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	40 in	101.6 cm
NOMINAL WEIGHT:	19.0 OZ/YD <sup>2</sup>	644 g/m <sup>2</sup>
NOMINAL THICKNESS:	0.030 in	0.762 mm
BASE FABRIC COUNT & WEAVE:	WARP: 19 yarns/in FILL: 14 yarns/in PLAIN WEAVE	WARP: 7.5 yarns/cm FILL: 5.5 yarns/cm PLAIN WEAVE
BASE CLOTH TEMPERATURE RESISTANCE:	1000° F	538° C
ALUMINIZED POLYESTER FILM TEMPERATURE RESISTANCE:	450° F	232° C
ADHESIVE TEMPERATURE RESISTANCE:	450° F	232° C

### PRODUCT HIGHLIGHTS

- ❖ Base Fabric Content: 100% Fiberglass Yarns.
- ❖ Base Fabric Finish: Plain or 9383 (Heat Cleaned).
- ❖ Fabric Finish: Aluminized Polyester Film on one side for Reflectivity.
- ❖ Width of finished product may be narrower due to the lamination process.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.