



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-SIL

AMI-SIL TAPE
STYLE #AS18-PSA
04/18

STYLE NO: AS18-PSA

NOMINAL BASE FABRIC THICKNESS: 0.030"

STANDARD PUT UP: 150FT/RL

STANDARD NOMINAL WIDTHS: 1", 1.5", 2", 3", 4", 5"

PLAIN TAPE TEMPERATURE RESISTANCE: 1800°F

ADHESIVE* TEMPERATURE RESISTANCE: 300°F

CONTENT: 96% SILICA (MINIMUM) WITH PRESSURE SENSITIVE ADHESIVE

WEAVE: 4 HARNESS CROWSFOOT

*ADHESIVE IS ONLY USED TO AID THE INSTALLATION PROCESS. AFTER THE TAPE IS IN PLACE, IT IS USUALLY MECHANICALLY BONDED (BY BOLT OR WIRE) SO THAT THE ADHESIVE IS NO LONGER NECESSARY.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03

Date Revised: 04/18/18

Date Reviewed: 04/18/18

Revision No.: 3

DOCUMENT IS UNCONTROLLED IF PRINTED