

AMI-SIL

AMI-SIL CLOTH
STYLE #AS2400
01/19

STYLE: AS2400

NOMINAL WIDTHS: 36", 60"

NOMINAL WEIGHT: 24.0 OZ/YD²

NOMINAL THICKNESS: 0.040"

TEMPERATURE RESISTANCE: 1800°F

MELTING POINT: 3000°F

CONTENT: 96% SILICA (MINIMUM)

WEAVE: HERRINGBONE

COUNT: WARP: 30
FILL: 22



THIS PRODUCT HAS BEEN TESTED AND FM APPROVED AS A *WELDING CURTAIN* TO ANSI/FM 4950 FOR HOT WORK PROTECTION. TEST DATA AVAILABLE UPON REQUEST. REFERENCE PROJECT ID # 3015367.

SPECIAL MARKINGS: PRODUCT MARKED IN ACCORDANCE WITH FM APPROVAL STANDARD 4950 INCLUDING DESIGNATION AS A ***WELDING CURTAIN*** AND WITH USES AND LIMITATIONS INFORMATION.

NOTE: ABRASION RESISTANT COATING AVAILABLE FOR ADDED DURABILITY. STANDARD COLORS FOR AR COATING ARE BLACK AND ORANGE

OTHER PIGMENTED COLORS AVAILABLE: BLACK

MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.