

Auburn Manufacturing Inc. P.O. Box 220 Mechanic Falls, Maine 04256 U.S.A. 1-800-AMI-6689 • 207-345-8271 FAX: 207-345-3380

AMI-SIL

AMI-SIL BRAIDED ROPE STYLE #ASBR 01/03

STYLE NO: ASBR

TEMPERATURE RESISTANCE: 1800°F

CONTENT: 96% SILICA (MINIMUM)

CONSTRUCTION: BRAIDED

| STYLE | DIAMETER | NOMINAL FT/LB | FT/CASE |
|----------|----------|------------------|--------------------|
| ASBR250 | 1/4" | 58.8 | 100 |
| ASBR375 | 3/8" | 27.0 | 100 |
| ASBR500 | 1/2" | 20.0 | 100 |
| ASBR750 | 3/4" | 10.2 | 100 |
| ASBR1000 | 1" | 7.0 | 75 |
| ASBR1375 | 1-3/8" | 2.8 | 90(2-45 FT PIECES) |
| ASBR2000 | 2" | 1.3 | 90(2-45 FT PIECES) |

NOTE: THERE MAY BE SEVERAL SPLICES PER CASE

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY

FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE

THEMSELVES WITH THE MSDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03 Date Revised: Date Reviewed: 09/08 Revision No.: 0