



Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET

AMI-SIL® Rope– Style No: ASR-HD

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA	DIAMETER	YIELD	CASE YIELD
ASR375HD	0.375 in / 9.53 mm	37.5 ft/lb / 25.2 m/kg	625 ft / 190m
ASR500HD	0.500 in / 12.70 mm	22.5 ft/lb / 15.1 m/kg	375 ft / 114m
ASR625HD	0.625 in / 15.88 mm	15.0 ft/lb / 10.1 m/kg	250 ft / 76m
ASR750HD	0.750 in / 19.05 mm	12.3 ft/lb / 8.3 m/kg	205 ft / 62m
ASR875HD	0.875 in / 22.23 mm	8.3 ft/lb / 5.6 m/kg	138 ft / 42m
ASR1000HD	1 in / 25.40 mm	6.8 ft/lb / 4.6 m/kg	113 ft / 34m
ASR1250HD	1.250 in / 31.75 mm	4.5 ft/lb / 3.0 m/kg	75 ft / 23m
ASR1500HD	1.500 in / 38.10 mm	3.0 ft/lb / 2.0 m/kg	50 ft / 15m
TEMPERATURE RESISTANCE:	1800° F / 982° C		

PRODUCT HIGHLIGHTS

- ❖ Content: 96% Silica (Minimum).
- ❖ Standard Color: White.
- ❖ Construction: Knitted.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.
- ❖ Note: There may be several splices per case.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.