Auburn Manufacturing Inc. P.O. Box 220 Mechanic Falls, Maine 04256 U.S.A. 1-800-AMI-6689 • 207-345-8271 FAX: 207-345-3380

AMI-SIL

AMI-SIL HIGH DENSITY ROPE STYLE #ASR-HD 10/18

STYLE NO: ASR-HD

TEMPERATURE RESISTANCE: 1800°F

CONTENT: 96% SILICA (MINIMUM)

CONSTRUCTION: KNITTED

STYLE	DIAMETER**	FT/LB**	FT/CASE **
ASR375HD	3/8"	37.5	625
ASR500HD	1/2"	22.5	375
ASR625HD	5/8"	15.0	250
ASR750HD	3/4"	12.3	205
ASR875HD	7/8"	8.3	138
ASR1000HD	1"	6.8	113
ASR1250HD	1 1/4"	4.5	75
ASR1500HD	1 1/2"	3.0	50

^{**} ALL VALUES ARE NOMINAL

NOTE: THERE MAY BE SEVERAL SPLICES PER CASE

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE

THEMSELVES WITH THE SDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03 Date Revised: 10/23/18 Date Reviewed: 10/23/18 Revision No.: 5