

Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET

EVER GREEN®– Style No: EVER GREEN CUT ‘N WRAP™ ET

For additional information please contact sales@auburnmfg.com

Description: EVER GREEN® CUT ‘N WRAP™ ET is an engineered insulating composite with a fiberglass inner core, high-performance-polymer coated woven glass fiber fabric outer layer and a woven glass inner (challenge side) layer.

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WEIGHT:	7.65 OZ/FT ²	2 kg/m ²
NOMINAL (EFFECTIVE) THICKNESS:	1.25 in	31.75 mm
MAXIMUM USE TEMPERATURE: HOT (CHALLENGE) SIDE.	700° F	371° C
FLAME SPREAD INDEX:	< 25	-----
SMOKE DEVELOPED INDEX:	< 50	-----
(ASTM E84) CLASSIFICATION:	A	-----
R / K VALUES:		
MEAN TEMPERATURE:		
100° F	3.32 R / 0.377 Btu-in/hr-ft ² -°F	0.58 RSI / 0.05 [W/(m*K)]
200° F	2.65 R / 0.470 Btu-in/hr-ft ² -°F	0.47 RSI / 0.07 [W/(m*K)]
300° F	2.13 R / 0.587 Btu-in/hr-ft ² -°F	0.38 RSI / 0.08 [W/(m*K)]
400° F	1.71 R / 0.732 Btu-in/hr-ft ² -°F	0.30 RSI / 0.10 [W/(m*K)]
500° F	1.37 R / 0.914 Btu-in/hr-ft ² -°F	0.24 RSI / 0.10 [W/(m*K)]

PRODUCT HIGHLIGHTS

- ❖ Insulation for pipe fittings and equipment.
- ❖ Standard Colors: Gray, AMI Signature Green®, White.
- ❖ Meets the requirements of ASTM C1695-10 (2015). **Standard Specification for Fabrication of Flexible Removable and Reusable Insulation for Hot Service.**



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.