



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-FLEX

AMI-FLEX TAPE
STYLE #FL16
07/18

MANUFACTURED IN U.S.
FROM IMPORTED and DOMESTIC
FIBERS

STYLE NO: FL16

NOMINAL THICKNESS: 0.060"

STANDARD PUT UP: 100FT/RL

STANDARD NOMINAL WIDTHS: 1", 1.5", 2", 3", 4", 5", 6"

TEMPERATURE RESISTANCE: 600°F

CONTENT: YARNS USED ARE A META-ARAMID/PARA-ARAMID BLEND OUTER LAYER WITH A FIBERGLASS INNER CORE

WEAVE: PLAIN

AVAILABLE WITH A HIGH PERFORMANCE PRESSURE SENSITIVE ADHESIVE

- ADHESIVE TEMPERATURE RESISTANCE: 300°F
- ADHESIVE IS ONLY USED TO AID THE INSTALLATION PROCESS, AFTER THE MATERIAL IS IN PLACE, IT IS USUALLY MECHANICALLY BONDED SO THAT THE ADHESIVE IS NO LONGER NECESSARY.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

PRODUCTS ARE INTENDED FOR COMMERCIAL USE AND SHOULD NOT BE LAUNDERED.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03

Date Revised: 07/26/18

Date Reviewed: 07/26/18

Revision No.: 4

DOCUMENT IS UNCONTROLLED IF PRINTED