



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI FLEX

AMI-FLEX CLOTH
STYLE# FL1700
10/18/22

MANUFACTURED IN U.S.
FROM IMPORTED and DOMESTIC FIBERS

STYLE #: FL1700

NOMINAL WIDTH: 40" OR 60"

NOMINAL WEIGHT: 17.0 OZ/YD²

NOMINAL THICKNESS: 0.065"

TEMPERATURE RESISTANCE: 600°F

CONTENT: YARNS USED ARE A META-ARAMID/PARA-ARAMID BLEND OUTER LAYER WITH A FIBERGLASS INNER CORE

WEAVE: PLAIN

COUNT: WARP: 20
FILL: 11

CUT RESISTANCE RATING: A6
(ASTM F2992/ANSI-ISEA105-2016)

RAVEL RESISTANCE COATING AVAILABLE - SEE COATINGS SPEC SHEET FOR OPTIONS.

NOTE: COATING FINISHES DECOMPOSE AT TEMPERATURES BELOW THE BASE FABRICS TEMPERATURE RESISTANCE.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

THIS PRODUCT IS INTENDED FOR COMMERCIAL USE AND SHOULD NOT BE LAUNDERED.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 03/06

Date Revised: 10/17/22

Date Reviewed: 10/18/22

Revision No.: 6

DOCUMENT IS UNCONTROLLED IF PRINTED