

Auburn Manufacturing Inc. P.O. Box 220 Mechanic Falls, Maine 04256 U.S.A. 1-800-AMI-6689 • 207-345-8271

Revision No.: 4

FAX: 207-345-3380

AMI-FLEX

MANUFACTURED IN U.S. FROM IMPORTED and DOMESTIC FIBERS

AMI-FLEX CLOTH STYLE# FL3300 07/18

STYLE #: FL3300

DESCRIPTION: HIGH QUALITY, HEAVY WEIGHT CLOTH, COMPRISED OF YARNS MADE WITH A

FIBERGLASS CORE AND CORE-SPUN WITH 100% ARAMID FIBER

NOMINAL WIDTH: 50"

NOMINAL WEIGHT: 33.0 OZ/YD²

NOMINAL THICKNESS*1: 0.102"

BASE FABRIC: PLAIN WEAVE; CORE-SPUN, TWO- PLY YARNS IN WARP AND FILL DIRECTIONS

ARAMID TEMPERATURE RESISTANCE: 600°F

GLASS CORE TEMPERATURE RESISTANCE: 1000°F

YARN COMPOSITION*2: 75% FIBERGLASS; 25% ARAMID FIBER

*1: ASTM D-1777-96 OPTION 1

*2: LOI 25% NOMINAL; ASTM D-4963-99

NOTE: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD

ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

THIS PRODUCT IS INTENDED FOR COMMERCIAL USE AND SHOULD NOT BE LAUNDERED.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 02/06 Date Revised: 07/26/18 Date Reviewed: 07/26/18