

Auburn Manufacturing Inc. P.O. Box 220 Mechanic Falls, Maine 04256 U.S.A. 1-800-AMI-6689 • 207-345-8271 FAX: 207-345-3380

AMI-FLEX

AMI-FLEX CLOTH STYLE# FLHB2200 07/18

MANUFACTURED IN U.S. FROM IMPORTED and DOMESTIC FIBERS

STYLE #: FLHB2200

NOMINAL WIDTH: 40" OR 60"

NOMINAL WEIGHT: 22.0 OZ/YD²

NOMINAL THICKNESS: 0.080"

TEMPERATURE RESISTANCE: 600°F

- CONTENT: YARNS USED ARE A META-ARAMID/PARA-ARAMID BLEND OUTER LAYER WITH A FIBERGLASS INNER CORE
- WEAVE: HERRINGBONE
- COUNT: WARP: 20 FILL: 12.5

Date of issue:

03/06

RAVEL RESISTANCE COATING AVAILABLE - SEE COATINGS SPEC SHEET FOR OPTIONS.

- NOTE: COATING FINISHES DECOMPOSE AT TEMPERATURES BELOW THE BASE FABRICS TEMPERATURE RESISTANCE.
- OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

THIS PRODUCT IS INTENDED FOR COMMERCIAL USE AND SHOULD NOT BE LAUNDERED.

Revision No.: 5

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.