



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

CARBO-FLEX®

AMI-FLEX CLOTH
STYLE# FLP3000
08/13

STYLE #: FLP3000

DESCRIPTION: 100% PREOX NONWOVEN COMBINED WITH A FABRIC WOVEN FROM YARNS WITH A META-ARAMID/PARA-ARAMID BLEND OUTER LAYER AND A FIBERGLASS INNER LAYER.

NOMINAL WIDTH: 40" OR 60"

NOMINAL WEIGHT: 30.0 OZ/YD²

NOMINAL THICKNESS: 0.145"

TEMPERATURE RESISTANCE:	FIBERGLASS	1000°F
	ARAMID	600°F
	PREOX	500°F

TYPICAL BREAKING STRENGTH:	WARP:	200 POUNDS/INCH WIDTH
	FILL:	70 POUNDS/INCH WIDTH

NOTE: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 02/06

Date Revised: 10/28/09

Date Reviewed: 08/21/2013

Revision No.: 1

DOCUMENT IS UNCONTROLLED IF PRINTED