



**Made in USA of Domestic and/or Imported Materials**

**PRODUCT DATA SHEET**

AMI-FLEX® Rope – Style No: FLR

For additional information please contact [sales@auburnmfg.com](mailto:sales@auburnmfg.com)

TECHNICAL DATA			
STYLE	DIAMETER	YIELD	CASE YIELD
FLR125	0.125 in / 3.18 mm	320.0 ft/lb / 215 m/kg	4000 ft / 1219 m
FLR188	0.188 in / 4.78 mm	256.0 ft/lb / 172 m/kg	3200 ft / 975 m
FLR250	0.250 in / 6.35 mm	80.0 ft/lb / 54 m/kg	2000 ft / 610 m
FLR375	0.375 in / 9.53 mm	64.0 ft/lb / 43 m/kg	1600 ft / 488 m
FLR500	0.500 in / 12.70 mm	33.6 ft/lb / 23 m/kg	840 ft / 256 m
TEMPERATURE RESISTANCE:	600° F / 316° C		

**PRODUCT HIGHLIGHTS**

- ❖ Construction: Knitted.
- ❖ Content: Yarns are a blend of meta & para-aramid with fiberglass inner core.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.