

# Safety Data Sheet

## AMI-GLAS® GL, GLTW, GLR, AND GLT SERIES INCLUDES -9383 SERIES

1 | Page

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<u>Trade Names/Synonyms:</u>	AMI-GLAS®/Woven fiber glass in various forms - cloth, tapes, rope, blankets, tubing, tadpole, etc.
<u>Product Identification:</u>	GL, GLTW, GLR, and GLT series.
<u>Chemical Name/Synonyms:</u>	Continuous filament fiber glass/fibrous glass, glass fibers.
<u>Manufacturer's Name:</u>	Auburn Manufacturing, Inc P. O. Box 220 Mechanic Falls, ME 04256 1-800-264-6689

### 2. HAZARDS IDENTIFICATION

OSHA HCS Status: This product is not a hazardous chemical, as defined by OSHA at 29 CFR 1910.1200



#### Precautionary Statements:

- P281: Wear personal protective equipment as required
- P302: If on skin, wash with mild soap and running water
- P304: If inhaled, move individual to fresh air. Seek medical attention if irritation persists
- P305: If in eyes, flush eyes at least 15 minutes; seek medical attention if irritation persists

Hazard Statements: N/A

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Abstracts Service Number: 65997-17-3 (Fiberglass)

# Safety Data Sheet

## AMI-GLAS<sup>®</sup> GL, GLTW, GLR, AND GLT SERIES INCLUDES -9383 SERIES

2 | Page

### 3. COMPOSITION (CONT.)

<u>Hazardous Ingredients</u>	<u>Weight %</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>	<u>OTHER</u>
Fiberglass, continuous Filament	≥ 96.5	a.	5 mg/ m <sup>3</sup> .8 hr TWA (inhalable) 1 fiber/cm <sup>3</sup> 8-hr TWA (respirable)	3 x 10 <sup>6</sup> fibers/m <sup>3</sup> 10-hr TWA (NIOSH)
<u>Nonhazardous Ingredients</u>				
Sizing	≤ 3.5	-----	none established	-----

- a. OSHA has not established a specific PEL for fibrous glass. It is considered to be a "particulate not otherwise regulated" (PNOR) and is covered under the OSHA nuisance dust PEL's of 5 mg/m<sup>3</sup> for the respirable dust fraction and 15 mg/m<sup>3</sup> for the total dust fraction for an 8-hr TWA (Time Weighted Average).

### 4. FIRST AID MEASURES

- Inhalation: Move individual to fresh air. Seek medical attention if irritation persists.
- Skin Contact: Wash with mild soap and running water. Use a washcloth to help remove fibers. To avoid further irritation do not rub or scratch irritated areas. Rubbing or scratching may force fibers into the skin. Seek medical attention if irritation persists.
- Eye Contact: Flush eyes with flowing water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion: N/A. (Not Applicable)

### 5. FIRE FIGHTING MEASURES

- Extinguishing Equipment: water, foam, carbon dioxide, dry chemical
- Special Fire-Fighting Instructions: In a sustained fire, self contained breathing apparatus should be worn.
- Unusual Fire and Explosion Hazards: None known.

# Safety Data Sheet

## AMI-GLAS® GL, GLTW, GLR, AND GLT SERIES INCLUDES -9383 SERIES

3 | Page

### 6. ACCIDENTAL RELEASE MEASURES

**ACTION TO TAKE FOR SPILLS ( Use Appropriate Safety Equipment/PPE):**

For solid product, not applicable.

For dusts and fibers generated during fabrication, vacuum and containerize.

### 7. HANDLING, STORAGE AND DISPOSAL

Handling: See Section 8.

Storage: No special precautions necessary.

Disposal: Dispose in accordance with federal, state and local regulations as a solid nonhazardous waste.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: General dilution ventilation and/or local exhaust ventilation should be provided, as necessary, to maintain exposures below PEL's or TLV's. **Adequate ventilation must be provided at elevated temperatures.**

Respiratory Protection: A properly fitted NIOSH/MHSA approved disposable dust respirator such as the 3M model 8210 or model 9900 (in high humidity environments) or equivalent should be used when: high dust levels are encountered; the level of glass fibers in the air exceeds the OSHA permissible exposure limits; or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program and OSHA regulations under 29 CFR 1910.134.

Eye Protection: Safety glasses, goggles or face shields should be worn whenever fiberglass materials are being handled.

Protective Clothing: Wear loose fitting, long sleeved shirt that covers to the base of the neck, and long pants. Skin irritation from exposure to fiberglass is known to occur chiefly at pressure points such as around the neck, wrist and waist. Wear gloves when handling product.

Work/Hygienic Practices: Handle in accordance with good industrial hygiene and safety practices:

= Avoid unnecessary exposure to dusts and fibers

# Safety Data Sheet

## AMI-GLAS<sup>®</sup> GL, GLTW, GLR, AND GLT SERIES INCLUDES -9383 SERIES

4 | Page

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT.)

- = Remove fibers from skin after exposure
- = Be careful not to rub or scratch irritated areas. Rubbing or scratching may force the fibers into the skin. The fibers should be washed off. Use of barrier creams can, in some instances, be helpful.
- = Use vacuum equipment to remove fibers and dusts from clothing. **COMPRESSED AIR SHOULD NEVER BE USED.** Always wash work clothes separately and wipe out the washer/sink in order to prevent loose glass fibers from getting on other clothes.
- = Keep the work area clean of any dusts and fibers generated during fabrication. Use vacuum equipment to clean up dusts and fibers. Avoid sweeping or using compressed air as these techniques resuspend dusts and fibers into the air.
- = Have access to safety showers and eye wash fountains.
- = For professional use only. **Keep out of children's reach.**

Exposure Limits (TLVS): N/A

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Melting Point (Softening): 800°C      Boiling Point(°C): N/A (Not Applicable)

Specific Gravity (Bare Glass): 2.59      Percent Volatile: N/A

Vapor Pressure: (mm Hg): N/A      Vapor Density (Air = 1): N/A

Evaporative Rate (Ethyl Ether = 1): N/A      Solubility in Water: Not soluble

Appearance and Odor: White/off-white/tan colored solid with no odor.

pH: N/A      Relative Density: N/A

Upper/Lower Flammability or Exposure Limits: N/A

Freezing Point: N/A      Flash Point: N/A

Partition coefficient (n-octanol/water): N/A      Auto Ignition Temperature: N/A

Decomposition Temperature: N/A      Viscosity: N/A

# Safety Data Sheet

## AMI-GLAS® GL, GLTW, GLR, AND GLT SERIES INCLUDES -9383 SERIES

5 | Page

### 10. STABILITY AND REACTIVITY

Stability (Conditions to Avoid): Product is stable.

Stabilizers: N/A

Incompatibility (Materials to Avoid): None known.

Hazardous Decomposition Products: Sizings or binders may decompose in a fire. Primary decomposition products include carbon monoxide, carbon dioxide, other hydrocarbons and water.

Hazardous Polymerization: Will not occur.

Flash Point (°F): N/A (Not Applicable)

Auto Ignition Temperature (°F): N/A

Flammability Limits (%): LEL: N/A UEL: N/A

### 11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Inhalation and skin contact.

Health Hazards (Including acute and chronic effects and symptoms of overexposure):

<u>ACUTE:</u>	<u>Inhalation:</u>	Inhalation of dusts and fibers may result in irritation of the upper respiratory tract (mouth, nose and throat)
	<u>Skin Contact:</u>	Skin contact with dusts and fibers may produce itching and temporary mechanical irritation.
	<u>Eye Contact:</u>	Eye contact with fibers and dusts may produce temporary mechanical irritation.
	<u>Ingestion:</u>	Temporary mechanical irritation of the digestive tract. Observe individual. If symptoms develop, consult a physician.

CHRONIC: See carcinogenicity section below. There are no known health effects associated with chronic exposure to this product.

# Safety Data Sheet

## AMI-GLAS® GL, GLTW, GLR, AND GLT SERIES INCLUDES -9383 SERIES

6 | Page

### 11. TOXICOLOGICAL INFORMATION (CONT.)

#### CARCINOGENICITY:

Hazardous Ingredients: Listed as carcinogen by: ACGIH IARC NTP OSHA

Fiberglass continuous filament No No\* No No

\*IARC: In June, 1987 the International Agency for Research on Cancer (IARC) categorized fiberglass continuous filaments as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify fiberglass continuous filaments as a possible, probable, or confirmed cancer causing material.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Persons with a history of chronic respiratory or skin conditions that are aggravated by mechanical irritants may be at increased risk for worsening their condition from exposure during use of the product.

### 12. ECOLOGICAL INFORMATION

N/A

### 13. DISPOSAL CONSIDERATIONS

See Section 8 (if applicable)

### 14. TRANSPORT INFORMATION

N/A

### 15. REGULATORY INFORMATION

No products made by Auburn Manufacturing, Incorporated contain any California Proposition 65 Substances as of the 12/29/17 update or come in contact with California Propostion 65 Substances during the manufacturing process.

### 16. OTHER INFORMATION

SDS prepared  
Reviewed for content & accuracy

May 23, 2014  
March 4, 2022

# Safety Data Sheet

## **AMI-GLAS® GL, GLTW, GLR, AND GLT SERIES** **INCLUDES -9383 SERIES**

7 | Page

To the best of our knowledge, the information contained herein is accurate. The information provided is based upon data furnished by our suppliers. However, neither Auburn Manufacturing, Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. While believed to be reliable, the information or products are intended for use by skilled persons at their own risk. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.