



Made in USA of Domestic and/or Imported Materials PRODUCT DATA SHEET

AMI-GLAS® Tape- Style No: GL02

For additional information please contact sales@auburnmfg.com

| TECHNICAL DATA | IMPERIAL | METRIC |
|-------------------------|----------|-----------|
| NOMINAL WIDTHS: | 1 in | 2.5 cm |
| | 1.5 in | 3.8 cm |
| | 2 in | 5.1 cm |
| | 2.5 in | 6.4 cm |
| | 3 in | 7.6 cm |
| | 4 in | 10. cm |
| NOMINAL THICKNESS: | 0.500 in | 12.700 mm |
| TEMPERATURE RESISTANCE: | 1000° F | 538° C |

PRODUCT HIGHLIGHTS

- Content: 100% Fiberglass Yarns.
- Type: Plain.
- Standard Color: White.
- Standard Put-Up: 50 FT/RL.
- Weave: Two Layers of Plain.
- Uncoated fiberglass tapes are noncombustible per USCG 164.009.
- Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.