



Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET

AMI-GLAS®– Style No: GL1202

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	60 in	152.4 cm
NOMINAL WEIGHT:	12.0 OZ/YD ²	407 g/m ²
NOMINAL THICKNESS:	0.025 in	0.635 mm
BASE FABRIC COUNT & WEAVE:	WARP: 19 yarns/in FILL: 14 yarns/in MODIFIED PLAIN	WARP: 7.5 yarns/cm FILL: 5.5 yarns/cm MODIFIED PLAIN
TEMPERATURE RESISTANCE:	1000° F	538° C
ADHESIVE TEMPERATURE RESISTANCE:	300° F	149° C

PRODUCT HIGHLIGHTS

- ❖ Content: 100% Fiberglass Yarns.
- ❖ Fabric Finish: Plain or 9383 (Heat Cleaned).
- ❖ Standard Color: White, other colors available please call for details.
- ❖ Military Specifications: MIL-C-20079H, Type 1, Class 7 (with 9383 finish)
MIL-DTL-24244D(SH) (with 9383 finish)
- ❖ All uncoated fiberglass yarn fabrics are noncombustible meeting USCG 164.009.
- ❖ Available with a high-performance pressure sensitive adhesive up to 60" wide.
- ❖ Adhesive used for ease of installation. Additional mechanical bonding recommended.
- ❖ Ravel resistance coating available.
- ❖ Coatings decompose at temperatures below the fabric.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.