

AMI-GLAS

AMI-GLAS CLOTH
STYLE #GL1300
01/2020

Made in USA of Domestic & Imported Materials

STYLE NO: GL1300

FABRIC FINISH: PLAIN, 9383 (heat cleaned) PIGMENTED (Black, Orange, Red)

NOMINAL WIDTH: 60"

NOMINAL WEIGHT: 13.0 OZ/YD²

NOMINAL THICKNESS: 0.016"

TEMPERATURE RESISTANCE: 1000°F

CONTENT: 100% FIBERGLASS YARNS

WEAVE: 4 HARNESS SATIN

COUNT: WARP: 48
FILL: 31



THIS PRODUCT HAS BEEN TESTED AND FM APPROVED AS A *WELDING CURTAIN* TO ANSI/FM 4950 FOR HOT WORK PROTECTION. TEST DATA AVAILABLE UPON REQUEST. REFERENCE PROJECT ID # 3015367.

SPECIAL MARKINGS: PRODUCT MARKED IN ACCORDANCE WITH FM APPROVAL STANDARD 4950 INCLUDING DESIGNATION AS A **WELDING CURTAIN** AND WITH USES AND LIMITATIONS INFORMATION.

ALL UNCOATED FIBERGLASS FABRICS ARE NONCOMBUSTIBLE MEETING USCG 164.009-5(f)

AVAILABLE WITH A HIGH PERFORMANCE PRESSURE SENSITIVE ADHESIVE

- ADHESIVE TEMPERATURE RESISTANCE: 300°F
- ADHESIVE IS ONLY USED TO AID THE INSTALLATION PROCESS, AFTER THE MATERIAL IS IN PLACE, IT IS USUALLY MECHANICALLY BONDED SO THAT THE ADHESIVE IS NO LONGER NECESSARY.

RAVEL RESISTANCE COATING AVAILABLE - SEE COATINGS SPEC SHEET FOR OPTIONS.

NOTE: COATING FINISHES DECOMPOSE AT TEMPERATURES BELOW THE BASE FABRICS TEMPERATURE RESISTANCE.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 04/07

Date Revised: 01/15/20

Date Reviewed: 01/07/20

Revision No.: 6

DOCUMENT IS UNCONTROLLED IF PRINTED