

**Made in USA of Domestic and/or Imported Materials**

**PRODUCT DATA SHEET**


AMI-GLAS®– Style No: GL1300

For additional information please contact [sales@auburnmfg.com](mailto:sales@auburnmfg.com)

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	60 in	152.4 cm
NOMINAL WEIGHT:	13.0 OZ/YD <sup>2</sup>	441 g/m <sup>2</sup>
NOMINAL THICKNESS:	0.016 in	0.406 mm
BASE FABRIC COUNT & WEAVE:	WARP: 48 yarns/in FILL: 31 yarns/in 4 HARNESS SATIN WEAVE	WARP: 18.9 yarns/cm FILL: 12.2 yarns/cm 4 HARNESS SATIN WEAVE
TEMPERATURE RESISTANCE:	1000° F	538° C
ADHESIVE TEMPERATURE RESISTANCE:	300° F	149° C

**PRODUCT HIGHLIGHTS**

- ❖ Content: 100% fiberglass yarns.
- ❖ Fabric Finish: Plain, 9383 (heat cleaned), Pigmented (Black, Orange, Red).
- ❖ All uncoated fiberglass fabrics are noncombustible meeting USCG 164.009.
- ❖ Available with a high-performance pressure sensitive adhesive. Adhesive used for ease of installation. Additional mechanical bonding recommended.
- ❖ Ravel resistance coating available.
- ❖ Coatings decompose at temperatures below the base fabric.
- ❖ This product has been tested and FM Approved as a **Welding Curtain** to ANSI/FM 4950 for hot work protection. Test data available upon request. Reference project ID #3015367.
- ❖ Special Markings: Product marked in accordance with FM Approval standard 4950 including designation as a **Welding Curtain** and with uses and limitations information.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.