



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-GLAS

AMI-GLAS TAPE
STYLE #GL16
01/2020

MADE IN USA WITH DOMESTIC MATERIALS

STYLE NO: GL16 (PLAIN OR 9383 HEAT CLEANED)

TYPE: PLAIN OR BOLT HOLE

NOMINAL THICKNESS: 0.060" (BOLT HOLE TAPE MAY MEASURE DIFFERENTLY)

STANDARD PUT UP: 100FT/RL

STANDARD NOMINAL WIDTHS: .5", .625", .75", 1", 1.5", 2", 2.5", 3", 4", 5", 6", 7", 7.5"

TEMPERATURE RESISTANCE: 1000°F

STANDARD COLOR: WHITE, OTHER COLORS AVAILABLE PLEASE CALL FOR DETAILS

CONTENT: 100% FIBERGLASS YARNS

WEAVE: PLAIN

AVAILABLE WITH A HIGH PERFORMANCE PRESSURE SENSITIVE ADHESIVE

- ADHESIVE TEMPERATURE RESISTANCE: 300°F
- ADHESIVE IS ONLY USED TO AID THE INSTALLATION PROCESS, AFTER THE MATERIAL IS IN PLACE, IT IS USUALLY MECHANICALLY BONDED SO THAT THE ADHESIVE IS NO LONGER NECESSARY.

ALL UNCOATED FIBERGLASS TAPES ARE NONCOMBUSTIBLE MEETING USCG 164.009

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 11/07

Date Revised: 01/14/20

Date Reviewed: 01/07/20

Revision No.: 3

DOCUMENT IS UNCONTROLLED IF PRINTED