



Made in USA of Domestic and/or Imported Materials


PRODUCT DATA SHEET

AMI-GLAS® Tape– Style No: GL32

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTHS:	1 in	2.5 cm
	1.5 in	3.8 cm
	2 in	5.1 cm
	3 in	7.6 cm
	4 in	10.2 cm
	5 in	12.7 cm
	6 in	15.2 cm
NOMINAL THICKNESS:*	0.032 in	0.813 mm
TEMPERATURE RESISTANCE:	1000° F	538° C
ADHESIVE TEMPERATURE RESISTANCE:	300° F	149° C

PRODUCT HIGHLIGHTS

<ul style="list-style-type: none"> ❖ Content: 100% Fiberglass Yarns. ❖ Type: Plain or Bolt Hole. ❖ * Bolt Hole Tape May Measure Differently. ❖ Standard Color: White, Other colors available please call for details. ❖ Standard Put-Up: 100 FT/RL. ❖ Weave: Plain. ❖ Available with a high-performance pressure sensitive adhesive. ❖ Adhesive used for ease of installation. Additional mechanical bonding recommended. ❖ Uncoated fiberglass tapes are noncombustible per USCG 164.009. ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS. 	
---	---

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.