

Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET


GOLDENGLAS®– Style No: GLN2025

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	40 in 60 in	101.6 cm 152.4 cm
NOMINAL WEIGHT:	18.0 OZ/YD ²	610 g/m ²
NOMINAL FINISHED FABRIC WEIGHT:	21.0 OZ/YD ²	712 g/m ²
NOMINAL THICKNESS:	0.030 in	0.762 mm
BASIC FABRIC COUNT & WEAVE:	WARP: 19 yarns/in FILL: 14 yarns/in PLAIN WEAVE	WARP: 7.5 yarns/cm FILL: 5.5 yarns/cm PLAIN WEAVE
COATING TEMPERATURE RESISTANCE:	225° F	107° C
BASE CLOTH TEMPERATURE RESISTANCE:	1000° F	538° C

PRODUCT HIGHLIGHTS

- ❖ Base Cloth Content: 100% fiberglass yarns.
- ❖ Fabric Finish: Compounded neoprene rubber used on one side of the cloth and the other side dyed a light yellow (other colors available on request). Used to ease fabrication and increase abrasion resistance. Recommended for safety apparel, blankets, curtains, and shields. Also used as a moisture barrier.
- ❖ This product has been tested and FM Approved as a **Welding Curtain** to ANSI/FM 4950 for hot work protection. Test data available upon request. Reference project ID #3019908.
- ❖ Special Markings: Product marked in accordance with FM Approval standard 4950 including designation as a **Welding Curtain** and with uses and limitations information.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.
- ❖ Note: Must be used in a well-ventilated area.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.