



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

GOLDENGLAS®

NEOPRENE COATED
AMI-GLAS CLOTH
STYLE #GLN2401
09/2014

STYLE NO: GLN2401

NOMINAL BASE FABRIC WIDTH: 40", 60" & 72"

NOMINAL BASE FABRIC WEIGHT: 24.0 OZ/YD²

NOMINAL BASE FABRIC THICKNESS: 0.055"

SERVICE TEMPERATURE: COATING: 225°F
CLOTH: 1000°F

BASE FABRIC CONTENT: 100% FIBERGLASS YARNS

WEAVE: PLAIN

COUNT: WARP: 20
FILL: 11

NOMINAL FINISHED FABRIC WEIGHT: 27 OZ/YD²

FABRIC FINISH: COMPOUNDED NEOPRENE RUBBER USED ON ONE SIDE OF THE CLOTH AND THE OTHER SIDE DYED A LIGHT YELLOW (OTHER COLORS AVAILABLE UPON REQUEST). USED TO EASE FABRICATION AND INCREASE ABRASION RESISTANCE. RECOMMENDED FOR SAFETY APPAREL, BLANKETS, CURTAINS, AND SHIELDS. ALSO MAY BE USED AS A MOISTURE BARRIER



THIS PRODUCT HAS BEEN TESTED AND FM APPROVED AS A *WELDING CURTAIN* TO ANSI/FM 4950 FOR HOT WORK PROTECTION. TEST DATA AVAILABLE UPON REQUEST. REFERENCE PROJECT ID # 3019908.

SPECIAL MARKINGS: PRODUCT MARKED IN ACCORDANCE WITH FM APPROVAL STANDARD 4950 INCLUDING DESIGNATION AS A **WELDING CURTAIN** AND WITH USES AND LIMITATIONS INFORMATION.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

NOTE: MUST BE USED IN WELL-VENTILATED AREA

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 04/07

Date Revised: 09/14/14

Date Reviewed: 09/08/14

Revision No.: 3

DOCUMENT IS UNCONTROLLED IF PRINTED