



Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET

AMI-GLAS® Rope – Style No: GLR-HD

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA			
STYLE	DIAMETER	YIELD	CASE YIELD
GLR125HD	0.125 in / 3.18 mm	150.0 ft/lb / 100.8 m/kg	3750 ft / 1143 m
GLR188HD	0.1875 in / 4.76 mm	102.0 ft/lb / 68.5 m/kg	2550 ft / 777 m
GLR250HD	0.250 in / 6.35 mm	45.5 ft/lb / 30.6 m/kg	1138 ft / 347 m
GLR375HD	0.375 in / 9.53 mm	25.0 ft/lb / 16.8 m/kg	625 ft / 190 m
GLR500HD	0.500 in / 12.70 mm	15.0 ft/lb / 10.1 m/kg	375 ft / 114 m
GLR625HD	0.625 in / 15.88 mm	10.0 ft/lb / 6.7 m/kg	250 ft / 76 m
GLR750HD	0.750 in / 19.05 mm	7.6 ft/lb / 5.1 m/kg	205 ft / 62 m
GLR875HD	0.875 in / 22.23 mm	5.5 ft/lb / 3.7 m/kg	138 ft / 42 m
GLR1000HD	1 in / 25.40 mm	4.5 ft/lb / 3.0 m/kg	113 ft / 34 m
GLR1250HD	1.250 in / 31.75 mm	3.0 ft/lb / 2.0 m/kg	75 ft / 23 m
GLR1500HD	1.500 in / 38.10 mm	2.0 ft/lb / 1.3 m/kg	50 ft / 15 m
GLR2000HD	2 in / 50.80 mm	0.74 ft/lb / 0.50 m/kg	50 ft / 15 m
TEMPERATURE RESISTANCE:	1000° F / 538° C		

PRODUCT HIGHLIGHTS

- ❖ Content: 100% fiberglass yarns.
- ❖ Construction: Knitted.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.