



**Made in USA of Domestic and/or Imported Materials**

## PRODUCT DATA SHEET

AMI-GLAS® Rope – Style No: GLR-LD

For additional information please contact [sales@auburnmfg.com](mailto:sales@auburnmfg.com)

TECHNICAL DATA			
STYLE	DIAMETER	YIELD	CASE YIELD
GLR250LD	0.250 in / 6.35 mm	78.0 ft/lb / 52.4 m/kg	1950 ft / 594 m
GLR375LD	0.375 in / 9.53 mm	46.1 ft/lb / 31.0 m/kg	1153 ft / 351 m
GLR500LD	0.500 in / 12.70 mm	26.1 ft/lb / 17.5 m/kg	653 ft / 199 m
GLR625LD	0.625 in / 15.88 mm	17.3 ft/lb / 11.6 m/kg	433 ft / 132 m
GLR750LD	0.750 in / 19.05 mm	12.8 ft/lb / 8.6 m/kg	320 ft / 98 m
GLR875LD	0.875 in / 22.23 mm	7.3 ft/lb / 4.9 m/kg	183 ft / 56 m
GLR1000LD	1 in / 25.40 mm	6.2 ft/lb / 4.2 m/kg	155 ft / 47 m
GLR1250LD	1.250 in / 31.75 mm	3.7 ft/lb / 2.5 m/kg	93 ft / 28 m
GLR1500LD	1.500 in / 38.10 mm	2.5 ft/lb / 1.7 m/kg	63 ft / 19 m
TEMPERATURE RESISTANCE:	1000° F / 538° C		

### PRODUCT HIGHLIGHTS

- ❖ Content: 100% fiberglass yarns.
- ❖ Construction: Knitted.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.