



**Made in USA of Domestic and/or Imported Materials**

## PRODUCT DATA SHEET

AMI-GLAS® Tubing – Style No: GLT

For additional information please contact [sales@auburnmfg.com](mailto:sales@auburnmfg.com)

TECHNICAL DATA	IMPERIAL	METRIC
STYLE	INNER DIAMETER	INNER DIAMETER
GLT375	0.375 in	9.53 mm
GLT500	0.500 in	12.70 mm
GLT625	0.625 in	15.88 mm
GLT750	0.750 in	19.05 mm
GLT1000	1 in	25.40 mm
GLT1250	1.250 in	31.75 mm
GLT1500	1.500 in	38.10 mm
GLT1750	1.750 in	44.45 mm
GLT2000	2 in	50.80 mm
GLT2250	2.250 in	57.15 mm
GLT2500	2.500 in	63.50 mm
GLT3000	3 in	76.20 mm
GLT3500	3.500 in	88.90 mm
NOMINAL WALL THICKNESS:	0.060 in	1.524 mm
TEMPERATURE RESISTANCE:	1000° F	538° C

### PRODUCT HIGHLIGHTS

- ❖ Content: 100% Fiberglass Yarns.
- ❖ Plain Weave.
- ❖ Standard Put Up: 100 FT/RL.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.