



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

VEXTRA

VEXTRA CLOTH
STYLE #GLV2401
01/24/20

Made in USA of Domestic & Imported Materials

STYLE NO: GLV2401

NOMINAL BASE FABRIC WIDTH: 40", 60" OR 72"

NOMINAL BASE FABRIC WEIGHT: 24.0 OZ/YD²

NOMINAL COATED WEIGHT: 24.72 OZ/YD²

NOMINAL BASE FABRIC THICKNESS: 0.055"

BASE CLOTH: 100% FIBERGLASS YARNS

WEAVE: PLAIN

STANDARD COLOR: BRONZE

COUNT: WARP: 20
FILL: 11

TEMPERATURE RESISTANCE: FABRIC IS RATED AT 1000°F CONTINUOUS, REMAINS STABLE TO 1500°F WITH VERMICULITE COATING.

FABRIC FINISH: VERMICULITE IS AN INORGANIC, CHEMICALLY INERT, NONCOMBUSTIBLE & ODORLESS COATING

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

NOTE: WIDTH OF FINISHED PRODUCT MAY BE NARROWER DUE TO SHRINKAGE DURING COATING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 02/06

Date Revised: 01/24/20

Date Reviewed: 01/24/20

Revision No.: 2

DOCUMENT IS UNCONTROLLED IF PRINTED