



Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET

VEXTRA®Tape– Style No: GLV32

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	1 in	2.5 cm
	1.5 in	3.8 cm
	2 in	5.1 cm
	3 in	7.6 cm
	4 in	10.2 cm
	5 in	12.7 cm
	6 in	15.2 cm
NOMINAL THICKNESS:*	0.032 in	0.813 mm
WEAVE:	PLAIN	PLAIN
TEMPERATURE RESISTANCE:	1000° F	538° C
ADHESIVE TEMPERATURE RESISTANCE:	300° F	149° C

PRODUCT HIGHLIGHTS

- ❖ Content: 100% Fiberglass yarns coated with vermiculite.
- ❖ Type: Plain or Bolt Hole.
- ❖ *Bolt hole may measure differently.
- ❖ Coating: Vermiculite.
- ❖ Color: Bronze.
- ❖ Standard Put-Up: 100 FT/RL.
- ❖ Fabric is rated to 1000° F (538° C) continuous, remains stable to 1500° F (982° C) with vermiculite coating.
- ❖ Vermiculite is an inorganic, chemically inert, noncombustible & odorless coating.
- ❖ Available with a high-performance pressure sensitive adhesive.
- ❖ Adhesive used for ease of installation. Additional mechanical bonding recommended.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.
- ❖ Note: Width of finished product may be narrower due to shrinkage during coating.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.