



Auburn Manufacturing Inc.  
P.O. Box 220  
Mechanic Falls, Maine 04256  
U.S.A. 1-800-AMI-6689 • 207-345-8271  
FAX: 207-345-3380

## **AMI-FAB**

AMI-FAB  
PARA-ARAMID  
SEWING THREAD  
06/18

STYLE NO: KV50

NOMINAL DIAMETER: 0.26mm (0.0102")

YIELD: 8,000 YDS/LB(APPROX)

TEMPERATURE RESISTANCE: 650° F

CHAR TEMPERATURE: 800° F

FREEZE TEMPERATURE: -50° F

CONTENT: 100% PARA-ARAMID FIBERS

STANDARD PUT UP: 1 LB SPOOLS

AVERAGE BREAKING STRENGTH: 15 LBS

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

---

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 05/31/18

Date Revised:

Date Reviewed:

Revision No.: