

Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET


AMI-SIL® – Style No: SAS2400-1

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	36 in 60 in	91.4 cm 152.4 cm
NOMINAL WEIGHT:	29.0 OZ/YD ²	983 g/m ²
NOMINAL THICKNESS:	0.047 in	1.194 mm
BASE FABRIC COUNT & WEAVE:	WARP: 30 yarns/in FILL: 22 yarns/in HERRINGBONE WEAVE	WARP: 11.8 yarns/cm FILL: 8.7 yarns/cm HERRINGBONE WEAVE
BASE FABRIC TEMPERATURE RESISTANCE:	1800° F	982° C
COATING TEMPERATURE:	500° F	260° C
BASE FABRIC MELTING POINT:	3000° F	1649° C

PRODUCT HIGHLIGHTS

- ❖ Content: 96% Silica (Minimum). Cloth with cured silicone rubber on one side.
- ❖ Standard Coating Color: Red. Also available in Gray.
- ❖ NFPA 701/2015 Test Method 2. Test report on file.
- ❖ This product has been tested and FM Approved as a **Welding Blanket** to ANSI/FM 4950 for hot work protection Test data available upon request. Reference project ID # 3015367.
- ❖ Special Markings: Product marked in accordance with FM Approval standard 4950 including designation as a **Welding Blanket** and with uses and limitations information.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.