

# Safety Data Sheet

## AMI-FAB™ TGL-12,18, or 24 SEWING THREAD

1 | Page

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Names/Synonyms: AMI-FAB™ TGL-12, 18, or 24 sewing thread/PTFE coated fiber glass sewing thread.

Product Identification: AMI-FAB™ TGL-12, 18, or 24 sewing thread.

Chemical Name/Synonyms: Continuous filament fiber glass coated with polytetrafluoroethylene polymer/fibrous glass, glass fibers coated with perfluorocarbon polymer.

Manufacturer's Name: Auburn Manufacturing, Inc  
P. O. Box 220  
Mechanic Falls, ME 04256  
800-264-6689

### 2. HAZARDS IDENTIFICATION

OSHA HCS Status: Product is not a hazardous chemical as defined by OSHA Standard 29 CFR 1910.1200



#### Precautionary Statements:

P281: Wear personal protective equipment as required  
P302: If on skin, wash with mild soap and running water  
P304: If inhaled, move individual to fresh air. Seek medical attention if irritation persists  
P305: If in eyes, flush eyes at least 15 minutes; seek medical attention if irritation persists

Hazard Statements: N/A

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Hazardous Ingredients</u>	<u>Weight %</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>	<u>OTHER</u>
Fiberglass, continuous filament	proprietary	a.	5 mg/ m <sup>3</sup> .8 hr TWA (inhalable) 1 fiber/cm <sup>3</sup> 8-hr TWA (respirable)	3 x 10 <sup>6</sup> fibers/m <sup>3</sup> 10-hr TWA (NIOSH)

# Safety Data Sheet

## AMI-FAB™ TGL-12,18, or 24 SEWING THREAD

2 | Page

### 3. COMPOSITION / INFORMATION ON INGREDIENTS (CON'T)

#### Nonhazardous Ingredients

Sizing	≤ 3.5	-----none established-----
Polytetrafluoroethylene	proprietary	-----not known-----

a. OSHA has not established a specific PEL for fibrous glass. It is considered to be a "particulate not otherwise regulated" (PNOR) and is covered under the OSHA nuisance dust PEL's of 5 mg/m<sup>3</sup> for the respirable dust fraction and 15 mg/m<sup>3</sup> for the total dust fraction for an 8-hr TWA (Time Weighted Average).

### 4. FIRST AID MEASURES

Inhalation: Move individual to fresh air. Seek medical attention if irritation persists.

Skin Contact: Wash with mild soap and running water. Use a washcloth to help remove fibers. To avoid further irritation do not rub or scratch irritated areas. Rubbing or scratching may force fibers into the skin. Seek medical attention if irritation persist

Eye Contact: Flush eyes with flowing water for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion: N. A. (Not Applicable)

Note to Physician: Inhaling fumes of the decomposition products of polytetrafluoroethylene can induce temporary influenza-like symptoms which are described as "polymer fume fever". These symptoms include fever, cough and malaise.

### 5. FIRE FIGHTING MEASURES

Extinguishing Media: Water, foam, carbon dioxide, dry chemical

Special Fire-Fighting Instructions: In a sustained fire, self contained breathing apparatus should be worn. Combustion is not self-sustaining, however, decomposition products burn above 690° C (1274° F). In the absence of external fuel employ protection for HF and other combustion fumes.

Unusual Fire and Explosion Hazards: Products will emit toxic fumes at high temperatures.

# Safety Data Sheet

## AMI-FAB™ TGL-12,18, or 24 SEWING THREAD

3 | Page

### 6. ACCIDENTAL RELEASE MEASURES

ACTION TO TAKE FOR SPILLS ( Use Appropriate Safety Equipment/PPE):

For solid product, not applicable.

For dusts and fibers generated during fabrication, vacuum and containerize.

### 7. HANDLING, STORAGE AND DISPOSAL

Handling: See Section 8.

Storage: No special precautions necessary.

Disposal: Dispose in accordance with federal, state and local regulations as a solid nonhazardous waste. Do not incinerate polytetrafluoroethylene (PTFE) waste.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: General dilution ventilation and/or local exhaust ventilation should be provided, as necessary, to maintain exposures below PEL's or TLV's. **Adequate ventilation must be provided at elevated temperatures and local exhaust necessary when heated above 300°C.**

Respiratory Protection: A properly fitted NIOSH/MHSA approved disposable dust respirator such as the 3M model 8210 or model 9900 (in high humidity environments) or equivalent should be used when: high dust levels are encountered; the level of glass fibers in the air exceeds the OSHA permissible exposure limits; or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program and OSHA regulations under 29 CFR 1910.134.

Eye Protection: Safety glasses, goggles or face shields should be worn whenever fiberglass materials are being handled.

Protective Clothing: Wear loose fitting, long sleeved shirt that covers to the base of the neck, and long pants. Skin irritation from exposure to fiberglass is known to occur chiefly at pressure points such as around the neck, wrist and waist. Wear gloves when handling product.

Work/Hygienic Practices: Handle in accordance with good industrial hygiene and safety practices:

= **Enforce no smoking rule in areas where polytetrafluoroethylene (PTFE) is handled or stored. Wash hands and face after handling to avoid transfer of polytetrafluoroethylene (PTFE) onto cigarettes and tobacco.**

= Avoid unnecessary exposure to dusts and fibers

= Remove fibers from skin after exposure

# Safety Data Sheet

## AMI-FAB™ TGL-12,18, or 24 SEWING THREAD

4 | Page

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CON'T)

- = Be careful not to rub or scratch irritated areas. Rubbing or scratching may force the fibers into the skin. The fibers should be washed off. Use of barrier creams can, in some instances, be helpful.
- = Use vacuum equipment to remove fibers and dusts from clothing. **COMPRESSED AIR SHOULD NEVER BE USED.** Always wash work clothes separately and wipe out the washer/sink in order to prevent loose glass fibers from getting on other clothes.
- = Keep the work area clean of any dusts and fibers generated during fabrication. Use vacuum equipment to clean up dusts and fibers. Avoid sweeping or using compressed air as these techniques resuspend dusts and fibers into the air.
- = Have access to safety showers and eye wash fountains.
- = For professional use only. **Keep out of children's reach.**

Exposure Limits (TLVS):

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Melting Point (Softening): NM                      Boiling Point(°C): N/A (Not Applicable)

Specific Gravity (Bare Glass): NM                      Percent Volatile: N/A

Vapor Pressure: (mm Hg): N/A                      Vapor Density (Air = 1): N/A

Evaporative Rate (Ethyl Ether = 1): N/A                      Solubility in Water: Not soluble

Appearance and Odor: White/off-white/tan colored solid with no odor.

pH: N/A    Relative Density: N/A

Upper/Lower Flammability or Exposure Limits: N/A

Freezing Point: N/A    Flash Point: N/A

Partition coefficient (n-octanol/water): N/A                      Auto Ignition Temperature: N/A

Decomposition Temperature: N/A                      Viscosity: N/A

# Safety Data Sheet

## AMI-FAB™ TGL-12,18, or 24 SEWING THREAD

5 | Page

### 10. STABILITY AND REACTIVITY

Stability (Conditions to Avoid): Stable under normal conditions. Polytetrafluoroethylene (PTFE, Teflon) begins to decompose very slowly above 500° F. Decomposition increases rapidly above 750° F. and processing at these temperatures is not recommended.

Incompatibility (Materials to Avoid): Molten alkali metals.

Hazardous Decomposition Products: Sizings or binders may decompose in a fire. Primary decomposition products include carbon monoxide, carbon dioxide, other hydrocarbons and water. Decomposition of the polytetrafluoroethylene will produce tetrafluoroethylene (from 800° F.), hexafluoropropylene (from 825° F.), perfluoroisobutylene (from 885° F.), and carbonyl fluoride (from 930° F.).

Hazardous Polymerization: Will not occur.

Flash Point (°F): N/A (Not Applicable)

Auto Ignition Temperature (°F): N/A

Flammability Limits (%): LEL: N/A UEL: N/A

Extinguishing Media: Water, foam, carbon dioxide, dry chemical

### 11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Inhalation and skin contact.

Health Hazards (Including acute and chronic effects and symptoms of overexposure):

ACUTE: Inhalation: Inhalation of dusts and fibers may result in irritation of the upper respiratory tract (mouth, nose and throat). **Thermal decomposition fumes at temperatures above 300° C may cause flu-like symptoms if inhaled.**

Skin Contact: Skin contact with dusts and fibers may produce itching and temporary mechanical irritation.

Eye Contact: Eye contact with fibers and dusts may produce temporary mechanical irritation.

Ingestion: Temporary mechanical irritation of the digestive tract. Observe individual. If symptoms develop, consult a physician.

**Heating polytetrafluoroethylene above 500° F. can produce harmful fumes; above 800° F. the fumes are acutely very toxic and can induce death.**

# Safety Data Sheet

## AMI-FAB™ TGL-12,18, or 24 SEWING THREAD

6 | Page

### 11. TOXICOLOGICAL INFORMATION (CON'T)

CHRONIC: See carcinogenicity section below. There are no known health effects associated with chronic exposure to this product.

#### CARCINOGENICITY:

Hazardous Ingredients: Listed as carcinogen by: ACGIH IARC NTP OSHA

Fiberglass continuous filament No No\* No No

\*IARC: In June, 1987 the International Agency for Research on Cancer (IARC) categorized fiberglass continuous filaments as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify fiberglass continuous filaments as a possible, probable, or confirmed cancer causing material.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Persons with a history of chronic respiratory or skin conditions that are aggravated by mechanical irritants may be at increased risk for worsening their condition from exposure during use of the product.

### 12. ECOLOGICAL INFORMATION

N/A

### 13. DISPOSAL CONSIDERATIONS

See Section 8 (if applicable)

### 14. TRANSPORT INFORMATION

N/A

### 15. REGULATORY INFORMATION

N/A

### 16. OTHER INFORMATION

SDS Date prepared  
Reviewed for content & accuracy

May 23, 2014  
July 6, 2020

# Safety Data Sheet

## AMI-FAB™ TGL-12,18, or 24 SEWING THREAD

7 | Page

To the best of our knowledge, the information contained herein is accurate. The information provided is based upon data furnished by our suppliers. However, neither Auburn Manufacturing, Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. While believed to be reliable, the information or products are intended for use by skilled persons at their own risk. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.