

# Safety Data Sheet

## AMI-FAB™ AS SERIES SEWING THREAD

1 | Page

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<u>Trade Names/Synonyms:</u>	AMI-FAB™ AS Series sewing thread/PTFE coated silica sewing thread.
<u>Product Identification:</u>	AMI-FAB™AS Series sewing thread.
<u>Chemical Name/Synonyms:</u>	Continuous filament silicon dioxide (SiO <sub>2</sub> ) coated with polytetrafluoroethylene polymer /fibrous silica, amorphous silica chemical family, amorphous silica fibers coated with perfluorocarbon polymer.
<u>Manufacturer's Name:</u>	Auburn Manufacturing, Inc P. O. Box 220 Mechanic Falls, ME 04256 800-264-6689

### 2. HAZARDS IDENTIFICATION

OSHA HCS Status: Product is not a hazardous chemical as defined by OSHA Standard 29 CFR 1910.1200



#### Precautionary Statements:

- P281: Wear personal protective equipment as required
- P302: If on skin, wash with mild soap and running water
- P304: If inhaled, move individual to fresh air. Seek medical attention if irritation persists
- P305: If in eyes, flush eyes at least 15 minutes; seek medical attention if irritation persists

Hazard Statements: N/A

# Safety Data Sheet

## AMI-FAB™ AS SERIES SEWING THREAD

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Abstracts Service Number: N/A

<u>Hazardous Ingredients</u>	<u>Weight %</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>	<u>OTHER</u>
Silicone dioxide, continuous filament	> 90	a.	10 mg/ m3. 8-hr TWA	none known

#### Nonhazardous Ingredients

Polytetrafluoroethylene      proprietary      -----not known-----

a. OSHA has not established a specific PEL for fibrous silicone dioxide (amorphous silica). It is considered to be a "particulate not otherwise regulated" (PNOR) and is covered under the OSHA nuisance dust PEL's of 5 mg/m<sup>3</sup> for the respirable dust fraction and 15 mg/m<sup>3</sup> for the total dust fraction for an 8-hr TWA (Time Weighted Average). Chemically, AMI-SIL® is amorphous silica which has an OSHA limit of 20 mppcf or 80 mg/m<sup>3</sup>.

### 4. FIRST AID MEASURES

Inhalation:      Move individual to fresh air. Seek medical attention if irritation persists.

Skin Contact:      Wash with mild soap and running water. Use a washcloth to help remove fibers. To avoid further irritation do not rub or scratch irritated areas. Rubbing or scratching may force fibers into the skin. Seek medical attention if irritation persists.

Eye Contact:      Flush eyes with flowing water for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion:      N.A (Not Applicable)

### 5. FIRE FIGHTING MEASURES

Extinguishing Equipment:      Water, foam, carbon dioxide, dry chemical

Special Fire-Fighting Instructions:      In a sustained fire, self contained breathing apparatus should be worn. Combustion is not self-sustaining, however, decomposition products burn above 690o C (1274o F). In the absence of external fuel employ protection for HF and other combustion fumes.

Unusual Fire and Explosion Hazards:      None known.

# Safety Data Sheet

## AMI-FAB™ AS SERIES SEWING THREAD

3 | Page

### 6. ACCIDENTAL RELEASE MEASURES

ACTION TO TAKE FOR SPILLS ( Use Appropriate Safety Equipment/PPE):

For solid product, not applicable.

For dusts and fibers generated during fabrication, vacuum and containerize.

### 7. HANDLING, STORAGE AND DISPOSAL

Handling: See Section 8.

The toxicologic data indicate that these materials should be handled with caution. The handling practices described in Section 8 of this MSDS must be strictly followed.

Product which has been in service at elevated temperature ( > 1800o F ) may undergo partial conversion to cristobalite, a form of crystalline silica. This reaction occurs at the lining hot face. As a consequence, this material becomes more friable (brittle); special caution must be taken to minimize generation of airborne dust. The amount of cristobalite present will depend on the temperature and length in service.

IARC has recently reviewed the animal, human and other relevant experimental data on silica in order to critically evaluate and classify the cancer causing potential. Based on its review, IARC has now classified crystalline silica/cristobalite as a Group 1 carcinogen. Crystalline silica inhaled in the form of quartz or cristobalite from industrial sources was classified as ***carcinogenic to humans*** on the basis of a relatively large number of epidemiological studies that together provided ***sufficient evidence*** in humans for the carcinogenicity of inhaled crystalline silica under the conditions specified. Crystalline silica is also listed by the NTP as a substance reasonably anticipated to be a carcinogen. Special care should be taken when working with "used" material to minimize the generation of dust. The OSHA permissible exposure limit (PEL) for cristobalite is 0.05 mg/m<sup>3</sup> (resp.). The ACGIH threshold limit value (TLV) for cristobalite is 0.05 mg/m<sup>3</sup> (resp.). (ACGIH 1989 - 90). If exposure limits are exceeded or if irritation is experienced, NIOSH approved respiratory protection should be worn. NIOSH approved respirator for particulates with a TLV of less than 0.05 mg/m<sup>3</sup> is generally acceptable, except that supplied air respirators are required for high airborne dust concentrations.

Storage: No special precautions necessary.

Disposal: Dispose of in accordance with federal, state and local regulations as a solid nonhazardous waste.

# Safety Data Sheet

## AMI-FAB™ AS SERIES SEWING THREAD

4 | Page

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: General dilution ventilation and/or local exhaust ventilation should be provided, as necessary, to maintain exposures below PEL's or TLV's. **Adequate ventilation must be provided at elevated temperatures and local exhaust is necessary when heated above 300°C.**

Respiratory Protection: A properly fitted NIOSH/MHSA approved disposable dust respirator such as the 3M model 8210 or model 9900 (in high humidity environments) or equivalent should be used when: high dust levels are encountered; the level of amorphous silic a fibers in the air exceeds the OSHA permissible exposure limits; or if irritation occurs. Use respiratory protection in accordance with your company's respiratory protection program and OSHA regulations under 29 CFR 1910.134.

Eye Protection: Wear safety glasses or chemical goggles to prevent eye contact. Contact lenses should not be worn unless chemical goggles are also used and care is taken not to touch the eyes with contaminated body parts or materials. Have eye washing facilities readily available where eye contact can occur.

Protective Clothing: Wear loose fitting, long sleeved shirt that covers to the base of the neck, and long pants. Skin irritation from exposure to amorphous silica is known to occur chiefly at pressure points such as around the neck, wrist and waist. Wear gloves when handling product.

Work/Hygienic Practices: Handle in accordance with good industrial hygiene and safety practices:

- = **Avoid contaminating tobacco and smoking utensils.**
- = Avoid unnecessary exposure to dusts and fibers
- = Remove fibers from skin after exposure
- = Be careful not to rub or scratch irritated areas. Rubbing or scratching may force the fibers into the skin. The fibers should be washed off. Use of barrier creams can, in some instances, be helpful.
- = Use vacuum equipment to remove fibers and dusts from clothing. **COMPRESSED AIR SHOULD NEVER BE USED.** Always wash work clothes separately and wipe out the washer/sink in order to prevent loose glass fibers from getting on other clothes.
- = Keep the work area clean of any dusts and fibers generated during fabrication. Use vacuum equipment to clean up dusts and fibers. Avoid sweeping or using compressed air as these techniques resuspend dusts and fibers into the air.
- = Have access to safety showers and eye wash fountains.
- = For professional use only. **Keep out of children's reach.**

# Safety Data Sheet

## AMI-FAB™ AS SERIES SEWING THREAD

5 | Page

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<u>Melting Point (Softening):</u> >3000°F base yarn only	<u>Boiling Point(°C):</u> N/A (Not Applicable)
<u>Specific Gravity (Bare Glass):</u> NM	<u>Percent Volatile:</u> N/A
<u>Vapor Pressure:</u> (mm Hg): N/A	<u>Vapor Density</u> (Air = 1): N/A
<u>Evaporative Rate</u> (Ethyl Ether = 1): N/A	<u>Solubility in Water:</u> Not soluble
<u>Appearance and Odor:</u> White/off-white/tan colored solid with no odor.	
<u>pH:</u> N/A	<u>Relative Density:</u> N/A
<u>Upper/Lower Flammability or Exposure Limits:</u> N/A	
<u>Freezing Point:</u> N/A	<u>Flash Point:</u> N/A
<u>Partition coefficient (n-octanol/water):</u> N/A	<u>Auto Ignition Temperature:</u> N/A
<u>Decomposition Temperature:</u> N/A	<u>Viscosity:</u> N/A

### 10. STABILITY AND REACTIVITY

Stability (Conditions to Avoid): Product is stable.

Stabilizers: N/A

Incompatibility (Materials to Avoid): Molten alkali metals. Reacts with xenon hexafluoride to produce xenon trioxide. May react with hydrofluoric acid to produce silicon tetrafluoride gas. Avoid oxygen difluoride, chlorine trifluoride and hot phosphoric acid.

Hazardous Decomposition Products: Sizings or binders may decompose in a fire. Primary decomposition products include carbon monoxide, carbon dioxide, other hydrocarbons and water. Hydrogen fluoride and perfluorocarbon olefins may be evolved at temperatures above 300°C.

Hazardous Polymerization: Will not occur.

Flash Point (°F): N/A (Not Applicable)

Auto Ignition Temperature (°F): N/A

Flammability Limits (%):

LEL: N/A

UEL: N/A

# Safety Data Sheet

## AMI-FAB™ AS SERIES SEWING THREAD

6 | Page

### 11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Inhalation and skin contact.

Health Hazards (Including acute and chronic effects and symptoms of overexposure):

ACUTE:      Inhalation:      Inhalation of dusts and fibers may result in irritation of the upper respiratory tract (mouth, nose and throat) **Thermal Decomposition fumes at temperatures above 300° C may cause flu-like symptoms if inhaled.**

Skin Contact:      Skin contact with dusts and fibers may produce itching and temporary mechanical irritation.

Eye Contact:      Eye contact with fibers and dusts may produce temporary mechanical irritation.

Ingestion:      Temporary mechanical irritation of the digestive tract. Observe individual. If symptoms develop, consult a physician.

CHRONIC:      See carcinogenicity section below. There are no known health effects associated with chronic exposure to this product.

### CARCINOGENICITY:

Hazardous Ingredients:      Listed as carcinogen by: ACGIH IARC NTP OSHA

Silicone dioxide,      -----NO-----  
continuous filament

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Persons with a history of chronic respiratory or skin conditions that are aggravated by mechanical irritants may be at increased risk for worsening their condition from exposure during use of the product.

### 12. ECOLOGICAL INFORMATION

N/A

### 13. DISPOSAL CONSIDERATIONS

See Section 8 (if applicable).

# Safety Data Sheet

## AMI-FAB™ AS SERIES SEWING THREAD

7 | Page

### 14. TRANSPORT INFORMATION

N/A

### 15. REGULATORY INFORMATION

N/A

### 16. OTHER INFORMATION

SDS Date prepared:  
Reviewed for content & accuracy

September 12, 2014  
July 6, 2020

**To the best of our knowledge, the information contained herein is accurate. The information provided is based upon data furnished by our suppliers. However, neither Auburn Manufacturing, Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. While believed to be reliable, the information or products are intended for use by skilled persons at their own risk. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.**