



**Made in USA of Domestic and/or Imported Materials**

## PRODUCT DATA SHEET

AMI-TUF® Tapes– Style No: SGL17 Tapes

For additional information please contact [sales@auburnmfg.com](mailto:sales@auburnmfg.com)

**Description:** AMI-TUF tapes are a fiberglass base fabric which has been coated with our specially formulated silicone rubber compound. It provides greater abrasion puncture and tear resistance to our base fiberglass fabric. Silicone coated fiberglass fabric proves greater life, water and oil repellancy than uncoated fabrics while providing low smoke and flame retardancy.

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	1 in to 30 in	2.54 cm to 76.2 cm
NOMINAL STANDARD LENGTHS:	10 ft 25 ft 50 ft	3.1 m 7.6 m 15.2 m
NOMINAL THICKNESS:	0.016 in	0.406 mm
WEAVE:	SATIN	SATIN
TEMPERATURE RESISTANCE:	1000° F	538° C

### PRODUCT HIGHLIGHTS

- ❖ Base Fabric Content: 100% Fiberglass cloth with cured silicone rubber on two sides.
- ❖ Color & Coating: Gray Silicone.
- ❖ Although base fabric is rated to 1000° F (538° C) continuous operating temperature, silicone coating is rated to 500° F (260° C) on a continuous basis.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.