



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-TUF

AMI-TUF CLOTH
STYLE #SGL9000
01/03

STYLE NO: SGL9000

NOMINAL WIDTH: 40" or 60"

NOMINAL FINISHED FABRIC WEIGHT: 90.0 OZ/YD²

NOMINAL FINISHED FABRIC THICKNESS: 0.125"

COATING TEMPERATURE: 500⁰ F

BASE FABRIC TEMPERATURE RESISTANCE: 1000⁰ F

CONTENT: 100% FIBERGLASS CLOTH WITH CURED SILICONE RUBBER ON TWO SIDES

WEAVE: PLAIN

COUNT: WARP-10 FILL-7

AMI-TUF STYLE SGL9000 IS A FIBERGLASS BASE FABRIC WHICH HAS BEEN COATED WITH OUR SPECIALLY FORMULATED SILICONE RUBBER COMPOUND. IT PROVIDES GREATER ABRASION PUNCTURE AND TEAR RESISTANCE TO OUR BASE FIBERGLASS FABRIC. THIS HEAVY DUTY SILICONE COATED FIBERGLASS FABRIC PROVIDES GREATER LIFE, WATER AND OIL REPELLANCY THAN UNCOATED FABRICS WHILE PROVIDING LOW SMOKE AND FLAME RETARDANCY.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03

Date Revised:

Date Reviewed: 09/08

Revision No.: 0

DOCUMENT IS UNCONTROLLED IF PRINTED