



**Made in USA of Domestic and/or Imported Materials**

## PRODUCT DATA SHEET

AMI-GUARD®– Style No: SGLP14 – FIRE QUILT™ Composite


For additional information please contact [sales@auburnmfg.com](mailto:sales@auburnmfg.com)

**Description:** Stitched composite constructed of fiberglass mat between two layers of specially formulated silicone coated fiberglass.

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WEIGHT:	55.0 OZ/YD <sup>2</sup>	1864 g/m <sup>2</sup>
NOMINAL THICKNESS:	0.250 in	6.350 mm
FIBERGLASS MAT TEMPERATURE RESISTANCE:	1000° F	538° C
SILICONE COATED FABRIC TEMPERATURE RESISTANCE:	500° F	260° C

### PRODUCT HIGHLIGHTS

- ❖ Available in 4' x 4 and 4' x 8' Quilted Pads.
- ❖ Color: Black.
- ❖ Product has been approved as a **Welding Pad** under FM Approval standard 4950 for hot work protection. Performance-based standard and test report available upon request. Reference project ID# 3044328.
- ❖ Special Markings: Product marked in accordance with FM Approval standard including designation as a **Welding Pad** and with uses and limitations information.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.