



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-GUARD® FIRE QUILT™
10/2014

STYLE: FIRE QUILT SGLP14 COMPOSITE

DESCRIPTION: STITCHED COMPOSITE CONSTRUCTED OF FIBERGLASS MAT BETWEEN TWO LAYERS OF SPECIALLY FORMULATED SILICONE COATED FIBERGLASS.

AVAILABILITY: 4' X 4' QUILTED BLANKET

NOMINAL WEIGHT: 55 OZ/YD²

NOMINAL THICKNESS: 0.250"

COLOR: BLACK

TEMPERATURE RESISTANCE: FIBERGLASS MAT: 1000°F

SILICONE COATED FABRIC: 500°F



PRODUCT HAS BEEN APPROVED AS A *WELDING PAD* UNDER FM APPROVAL STANDARD 4950 FOR HOT WORK PROTECTION. PERFORMANCE-BASED STANDARD AND TEST REPORT AVAILABLE UPON REQUEST. REFERENCE PROJECT ID # 3044328.

SPECIAL MARKINGS: PRODUCT MARKED IN ACCORDANCE WITH FM APPROVAL STANDARD INCLUDING DESIGNATION AS A **WELDING PAD** AND WITH USES AND LIMITATIONS INFORMATION.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 05/2013

Date Revised: 10/2/14

Date Reviewed: 10/1/14

Revision No.: 1

DOCUMENT IS UNCONTROLLED IF PRINTED