

Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET

AMI-TUF®– Style No: SGLP1400


For additional information please contact sales@auburnmfg.com

Description: Silicone rubber compounded with proprietary minerals and pigment coated onto a fiberglass substrate.

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL WIDTH:	37 in 60 in	94.0 cm 152.4 cm
NOMINAL FINISHED FABRIC WEIGHT:	14.0 OZ/YD ²	475 g/m ²
NOMINAL FINISHED FABRIC THICKNESS:	0.015 in	0.381 mm
NOMINAL FABRIC COUNT:	WARP: 28 yarns/in FILL: 20 yarns/in	WARP: 11.0 yarns/cm FILL: 7.9 yarns/cm
NOMINAL BREAKING STRENGTH:	WARP: 150 LBS MIN AVG FILL: 100 LBS MIN AVG	WARP: 263 N/cm FILL: 175 N/cm
BASE FABRIC TEMPERATURE RESISTANCE:	1000° F	538° C

PRODUCT HIGHLIGHTS

- ❖ Content: 100% fiberglass cloth with cured silicone rubber on two sides.
- ❖ Standard color: Black.
- ❖ Although base fabric is rated to 1000°F continuous operating temperature, silicone coating is rated to 500°F on a continuous basis.
- ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.