



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-GLAS

SILICONE COATED
AMI-GLAS TUBING
STYLE #SGLT
10/08

STYLE NO: SGLT

NOMINAL WALL THICKNESS: 0.125"

STANDARD PUT UP: 3/8"-1 1/2": 100 FT/RL
1 3/4"-4": 50 FT/RL

TEMPERATURE RESISTANCE: 1000°F FIBERGLASS TUBE INSIDE
500°F-SILICONE COATING OUTSIDE
WILL WITHSTAND A SPLASH OF 3000°F MOLTEN-METAL

K VALUE BTU/DEGREES F/IN. OF THICKNESS: 1.2

CONTENT: FIBERGLASS YARNS WITH SILICONE COATING

WEAVE: BRAIDED

NOMINAL INNER DIAMETERS: 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1-1/4", 1-1/2", 1-3/4", 2", 2-1/4", 2-1/2", 2-3/4", 3", 3-1/4", 3-1/2", 3-3/4", 4"

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03

Date Revised: 10/08

Date Reviewed: 08/08

Revision No.: 1

DOCUMENT IS UNCONTROLLED IF PRINTED