



Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET


VEXTRA®– Style No: SGLV3001-1-TP

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA	IMPERIAL	METRIC
NOMINAL BASE FABRIC WIDTH:	40 in 60 in	101.6 cm 152.4 cm
NOMINAL BASE FABRIC WEIGHT:	39.0 OZ/YD ²	1322 g/m ²
NOMINAL BASE FABRIC THICKNESS:	0.070 in	1.778 mm
BASE FABRIC COUNT & WEAVE:	WARP: 19 yarns/in FILL: 8 yarns/in PLAIN WEAVE	WARP: 7.5 yarns/cm FILL: 3.1 yarns/cm PLAIN WEAVE
TEMPERATURE RESISTANCE (continuous):	1000° F	538° C
STABLE TO:	1500° F	816° C
SILICONE COATING RATED TO:	500° F	260° C

PRODUCT HIGHLIGHTS

- ❖ Content: 100% fiberglass cloth treated with vermiculite and coated on one side with a silicone rubber compound.
- ❖ Vermiculite is an inorganic, chemically inert, noncombustible, & odorless coating.
- ❖ Silicone coating is rated to 500°F (260°C) continuous. Product remains stable to 1500°F (816°C) due to the vermiculite coating.
- ❖ Material should be tested for its suitability in any application, particularly flexing applications at elevated temperatures. Users should also familiarize themselves with the SDS.
- ❖ Note: Width of finished product may be narrower due to shrinkage during coating.



ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.