



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-TUF

AMI-TUF CLOTH
STYLE #TGL165
10/09

STYLE NO: TGL165

NOMINAL WIDTH: 60"

NOMINAL FINISHED FABRIC WEIGHT: 16.5 OZ/YD²

NOMINAL FINISHED FABRIC THICKNESS: 0.017"

BASE FABRIC TEMPERATURE RESISTANCE: 1000⁰ F

COATING TEMPERATURE RESISTANCE: 550⁰ F

BASE FABRIC: FIBERGLASS

COATING/COLOR: PTFE(polytetrafluoroethylene)/GRAY-OTHER COLORS AVAILABLE

TENSILE STRENGTH: 400 LBS/INCH MIN AVG-WARP
350 LBS/INCH MIN AVG-FILL

Meets the requirements of ASTM C1695-09, **Standard Specification for Fabrication of Flexible Removable and Reusable Insulation for Hot Service**

AMI-TUF STYLE TGL165 IS A PTFE COATED/IMPREGNATED FIBERGLASS CLOTH WITH A HEAVIER PTFE COATING ON ONE SIDE. THE FORMULATED PTFE COMPOUND PROVIDES IMPROVED WATER, OIL, CHEMICAL AND ABRASION RESISTANCE OVER UNCOATED FABRIC WHILE STILL OFFERING TEMPERATURE RESISTANCE UP TO 550⁰ F.

NOTE: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03

Date Revised: 10/27/09

Date Reviewed: 10/27/09

Revision No.: 2

DOCUMENT IS UNCONTROLLED IF PRINTED