


Made in USA of Domestic and/or Imported Materials

PRODUCT DATA SHEET

VEXTRA® – Style No: Tadpole Tapes

For additional information please contact sales@auburnmfg.com

TECHNICAL DATA		
NOMINAL WIDTHS:	1.000 in / 2.5 cm	2.000 in / 5.1 cm
	1.125 in / 2.9 cm	2.375 in / 6.0 cm
	1.250 in / 3.2 cm	2.500 in / 6.4 cm
	1.375 in / 3.5 cm	2.625 in / 6.7 cm
	1.500 in / 3.8 cm	2.750 in / 7.0 cm
	1.750 in / 4.5 cm	3.000 in / 7.6 cm
	1.875 in / 4.8 cm	
NOMINAL BULB DIAMETERS:	0.375 in / 9.53 mm	
	0.500 in / 12.70 mm	
	0.625 in / 15.88 mm	
	0.750 in / 19.05 mm	
	1.000 in / 25.4 mm	
	1.500 in / 38.10 mm	
NOMINAL TAIL THICKNESS:	0.125 in / 3.18 mm	
NOMINAL WALL THICKNESS OF BULB:	0.060 in / 1.52 mm	
TEMPERATURE RESISTANCE:	1000° F / 538°C	

PRODUCT HIGHLIGHTS	
<ul style="list-style-type: none"> ❖ Content: 100% fiberglass yarns. Coated with vermiculite. ❖ Standard Put Up: 100 FT Lengths. ❖ Construction: Jacket-Woven, Bulb-Knitted fiberglass rope. ❖ Vermiculite is an inorganic, chemically inert, noncombustible & odorless coating. Note: Fiberglass rope core inside bulb is not coated. ❖ Tape is rated at 1000° F (538° C) continuous, remains stable to 1500° F (816° C) with vermiculite coating. ❖ Material should be tested for its suitability in any application. Users should also familiarize themselves with the SDS. 	

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY THEMSELVES THAT THE RECOMMENDATIONS ARE SUITABLE FOR THEIR USE AND MEET ALL APPROPRIATE SAFETY & HEALTH STANDARDS.